

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**



FIG. 6 (PRIOR ART)  
USPN 6,360,965

FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D




FIG. 7 (PRIOR ART)  
USPN 4,052,002




FIG. 8A (PRIOR ART)  
USPN 4,151,955




FIG. 8B





FIG. 9 (PRIOR ART)  
USPN 4,151,955




FIG. 13




FIG. 10




FIG. 11





FIG. 14



Fluidic Oscillator Operating Conditions:

(@ 1 l/min and 10 psi)

Avg. Droplet Diameter

= 1.7-1.9 mm

Avg. Droplet Speed

= 4.1-4.4 m/sec

Oscillation Frequency

= 45-50 Hz

FIG. 15A






FIG. 15B



**FIG. 28A**



**FIG. 28B**




FIG. 29

